## WHITTEMORE COMPANY MATERIAL SAFETY DATA SHEET

## **SECTION 1 - Chemical Product and Company Identification**

Product Identifier: Perlite, All Grades: Super Coarse, Medium Grade, Loose Fill Insulation, Concrete Grade, 148,146,130, 50/100, 720, LF, 000, # 100, #101, #200 Product Class: Amorphous Sodium Potassium Aluminum Silicate Product Use: Insulation, Construction, Industrial, and Horticultural Applications

## Whittemore Company, Inc.

30 Glenn Street Lawrence, MA 01843 Emergency Telephone Number: 978-681-8833 Fax Number: 978-682-3413

## Supplier's Name (if different)

- □ Street Address
- □ City, Province/State, Postal/Zip Code
- Emergency Telephone Number
- Fax Number

Preparation date of MSDS: October 17, 2011 MSDS Prepared By: Kenneth Wiener (Phone: 310-377-7977)

### **SECTION 2 – Composition/Information on Ingredients**

Product Description/Components: Expanded perlite powder or granules, CAS# 93763-70-3

<u>Hazardou</u>	<u>is</u>	<u>%</u>	ACGIH
Ingredien	ts <u>CAS#</u>		TLV, mg/cu.m. NIOSH, mg/cu.m OSHA PEL, mg/cu.m
Quartz	14808-60-7	<0.1	0.025 (Respirable) 0.05 (Respirable) 0.1 (Respirable)

LD50: Not Available LC50: Not Available

## **SECTION 3 – Hazards Identification**

Route of entry:

Skin contact: Repeated or prolonged contact may cause irritation

Skin absorption: N/A

Eye contact: May irritate or injure eyes, mechanically

Inhalation: Upper Respiratory Irritant: May aggravate pre-existing respiratory conditions. Long-term inhalation of respirable crystalline silica can cause disabling lung disease (silicosis).

Ingestion: LD50 not established, presumed over 2000 mg/kg

Emergency Overview: The fine particle size products represent inhalation hazards that can readily be controlled with appropriate dust protection equipment. Avoid processes that generate unnecessary dust.

WHMIS Symbols:



Potential Health Effects: See above regarding long term exposure: skin irritation, silicosis and eye irritation

## **SECTION 4 – First Aid Measures**

Skin Contact: Wash off with soap and water

Eye Contact: Flush eyes with generous amounts of water for at least 5 minutes. Inhalation: Remove to fresh air. Seek medical attention if victim is not breathing or uncomfortable. Ingestion: Do not induce vomiting. Seek medical attention if victim is not breathing or uncomfortable.

## **SECTION 5 - Fire Fighting Measures**

Flammable: No Means of Extinction: Use extinguishing media appropriate for surrounding material. Flashpoint (°C) and Method (oc or cc): N/A Upper Flammable Limit (% by volume): N/A Lower Flammable Limit (% by volume): N/A Autoignition Temperature (°C): N/A Explosion Data - Sensitivity to Impact: N/A Explosion Data - Sensitivity to Static Discharge: High airborne concentrations of dusts are susceptible to explosions. Hazardous Combustion Products: N/A NFPA: Health: \*(Refer to MSDS), Flammability: 0, Reactivity: 0, Other: None

HMIS Ratings: Health: \*(See MSDS), Flammability: 0, Reactivity: 0, Personal Protection: E

## **SECTION 6 - Accidental Release Measures**

Leak and Spill Procedures: Normal clean-up procedures. Care should be taken to avoid causing dust to become airborne. Vacuum cleaning systems are recommended. Wetting spilled material with water may control dust and make clean up easier.

# **SECTION 7 - Handling and Storage**

Handling Procedures and Equipment: Avoid creating unnecessary dust. Storage Requirements: Store with other dusty materials, away from products that could be affected by dust.

# **SECTION 8 - Exposure Control/Personal Protection COMMENTS**

Exposure Limits

ACGIH TLV: 10 mg/m<sup>3</sup> total dust

3 mg/m<sup>3</sup> respirable dust

OSHA PEL: 15 mg/m<sup>3</sup> total dust

5 mg/m<sup>3</sup> respirable dust

Engineering Controls

General: Good housekeeping rules apply

Local Exhaust from work stations using this material

Recommended Personal Protective Equipment:

Plastic or Rubber Gloves if skin irritation occurs

 Respirator – NIOSH/OSHA approved dust respirator adequate for contaminant concentrations encountered.

- Eye protection recommended
- Disposable footwear for frequent handling of this material
- Coveralls for frequent handling of this material

### **SECTION 9 – Physical and Chemical Properties**

Physical State: Solid powder or granules Odor and Appearance: White to off white powder or granules with no odor Odor Threshold (ppm): N/A Specific Gravity: 2.35 Vapor Density (air=1): N/A Vapor Pressure (mmHg): N/A Evaporation Rate: N/A Boiling Point (°C): N/A Freezing Point (°C): N/A PH: 6.5 – 7.5, as 10% slurry in distilled water Coefficient of Water/Oil Distribution: N/A Solubility in Water: Negligible

Visual Detection Method Only

### **SECTION 10 - Stability and Reactivity**

Chemically Stable?: Yes Incompatibility with other substances? Yes: Hydrofluoric acid (HF) Reactivity, and under what conditions?: Toxic silicon tetrafluoride gas will result with contact with hydrofluoric acid. Hazardous Decomposition Products: See above

#### **SECTION 11 - Toxicological Information**

Effects of Acute Exposure: Slightly hazardous in case of skin contact (irritant), of eye contact (irritant), or in case of inhalation (irritant).

Effects of Chronic Exposure:

Irritancy of Product: Potential IRRITANT for Skin Sensitization, Respiratory Sensitization: Upper Respiratory Irritant: May aggravate pre-existing respiratory conditions. Long-term inhalation of respirable crystalline silica can cause disabling lung disease (silicosis)

Carcinogenicity: These products contain less than 0.1% crystalline silica, and low percentages of particles of respirable size, hence present very low risk. IARC: Not reviewed ACGIH: PNOS (Particulates Not Otherwise Specified), Not carcinogenic Reproductive Toxicity: Not available Teratogenicity: Not established Embryotoxicity: Not available Mutagenicity: Ames: Not available

#### **SECTION 12 – Ecological Information**

Aquatic Toxicity: Low hazard for usual industrial or commercial handling. Approved for use in soils.

### **SECTION 13 – Disposal Considerations**

Waste Disposal: Dispose of this product in accordance with all applicable local, state and Federal regulations.

### **SECTION 14 – Transport Information**

Special Shipping Information DOT: No special requirements IMO: Non-hazardous ICAO: Non-hazardous

### **SECTION 15 – Regulatory Information**

WHMIS CLASSIFICATION: D2B (Toxic) OSHA: Label as required by Hazard Communication Standard 29 CFR 1910.1200 (f) and applicable state and local laws and regulations TSCA: Included as a naturally occurring material CANADA DSL: Included or exempt

### **SECTION 16 – Other Information**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by CPR.

Information provided in this document is believed to be accurate as of October 17, 2011 and may be subject to change without notice. The information is provided in good faith to comply with applicable federal and state laws. However, no warranty or representation with respect to such information is intended or given. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.